

ITEM NO.	ITEM TOTAL	ELDON-DUCKABUSH RECONDUCTOR MASTER MATERIAL LIST REV A - ISSUED FOR BID  			
		MATERIAL DESCRIPTION	VENDOR	PART NO.	UNIT COST
32	242	INSULATOR, POLY, VISE TOP, 15KV	HENDRIX	HPI-15VTP-01	\$ 26.74
116	168	DEAD END, STRAIN BOLTED 3/0-556	MACLEAN POWER	ASO-858-2-N	\$ 26.36
195	289	ANCHOR SHACKLE, 1/2 IN, 20KIP	MACLEAN POWER	ASH-45	\$ 9.25
247	6	SCREW, LAG 1/2 X 4	MACLEAN POWER	J8754TP	\$ 1.04
262	264	BOLT, ASSEMBLY S.S 1/2X2	MT. HOOD	BAS88.050C0200	\$ 5.69
282	85	BOLT, DOUBLE ARMING 5/8X18 IN.	MACLEAN POWER	J8868	\$ 2.98
294	6	BOLT, MACHINE 1/2X10 IN.	CHANCE	8710	\$ -
331	510	BOLT, MACHINE 3/4" X 16", SQ HEAD, W/ NUT, GALV	HUGHES BROTHERS	B716-6	\$ 5.92
332	6	BOLT, MACHINE 3/4X16 IN.	MACLEAN POWER	J8916	\$ 5.92
354	699	BOLT, MACHINE 5/8" X 16", SQ HEAD, W/ NUT, GALV	HUGHES BROTHERS	B616-6	\$ 1.80
379	144	BOLT, OVAL EYE 5/8X16 IN.	MACLEAN POWER	J9416	\$ 7.25
407	30	WASHER, DB COIL SPRING LOCK, 9/16" HOLE	CHANCE	C2050185	\$ 0.22
410	964	WASHER, DB COIL SPRING LOCK, 11/16" HOLE	HUGHES BROTHERS	SLW2-60	\$ 0.48
412	516	WASHER, DB COIL SPRING LOCK, 13/16" HOLE	HUGHES BROTHERS	SLW2-70	\$ 0.41
419	37	WASHER, ROUND 1-3/8", 9/16" HOLE	CHANCE	PS6803TDG	\$ 0.21
424	172	WASHER, ROUND 2" X 1/4", 11/16" HOLE	HUGHES BROTHERS	RW2-60	\$ 1.76
451	156	WASHER, SQ CURVE 3" X 3" X 1/4", 13/16" HOLE, GALV	HUGHES BROTHERS	SCW3-70	\$ 1.39
453	815	WASHER, SQ CURVE 3" X 3" X 1/4", 11/16" HOLE, GALV	HUGHES BROTHERS	SCW3-60	\$ 2.00
455	360	WASHER, SQ CUPPED 4" X 4" X 1/4", 13/16" HOLE, GALV	HUGHES BROTHERS	CW70	\$ 2.10
474	82	NUT, ANCHOR ROD 1 IN.	CHANCE	12585	\$ 17.00
484	11	NUT, OVAL EYE 5/8 IN.	MACLEAN POWER	J1092	\$ 3.60
487	11	NUT, OVAL EYE 3/4 IN.	MACLEAN POWER	J1093	\$ 2.75
520	82	ROD, ANCHOR 1 IN X 7 FT	CHANCE	12334P	\$ 48.00
545	86	GUY MARKER, YELLOW	PREFOMED	PLP PG-5518	\$ 4.00
606	2	WASHER, SINGLE COIL SPRING LOCK, 11/16" HOLE	HUGHES BROTHERS	SLW60	\$ -
627	476	STAPLE, GALV 1-1/2 X 1/4 IN	MACLEAN POWER	J1672 100LBS	\$ 0.08
633	15	ROD, GROUND 5/8 IN X 8 FT CU CLAD	CHANCE	615880	\$ 19.90
641	2	GROUNDING CAP, LB 200 AMP	ELASTIMOLD	160DRG	\$ 26.77
680	18	TERM. END, BR TERM 4/0-1000, 2 HOLE, 90D	TRAVIS PATTERN	11-110-90	\$ 71.35
770	92	ANGLE BRACKET, CLEVIS	MACLEAN POWER	J1300	\$ 7.72
805	55	PIN, POLE TOP STEEL 20 IN	MACLEAN POWER	J740Z	\$ 15.87
861	102	5' CROSSARM, FIBERGLASS, TANGENT	PUPI	TB1000060SPX2	\$ -
941	15	CONDUCTOR, BARE CU WELD 4A	---	4A CU WELD	\$ 1.11
942	291	CONDUCTOR, BARE CU, #4 STR.	---	4 BARE STR CU	\$ 1.22
950	225	CONDUCTOR, BARE OH 4 ACSR, SWANATE	---	SWANATE	\$ 0.15
956	525	CONDUCTOR, SEC. OH 2 TRIPLEX	---	COCKLE	\$ 0.90
958	70	CONDUCTOR, SEC. OH 1/0 TRIPLEX, JANTHINA	---	10494301 JANTHINA	\$ 1.35
960	75	CONDUCTOR, SEC. OH, 4/0 TRIPLEX, ZUZARA	---	4/0-3ACSR-ZUZARA-XLP	\$ 1.63
1014	3	CLAMP, HOT LINE, .502"-1.031", CU TO CU	MACLEAN	C1540	\$ -
1087	1	CONN., CU CRIMPIT YC2C2	PENN-UNION	CCT-22	\$ 1.75
1089	10	CONN., CU CRIMPIT YC2C2	HUBBELL	YC2C2	\$ 1.75
1094	86	CONN., CU CRIMPIT #6-#2	BURNDY	YGHC2C2	\$ 5.61
1145	1	CONN.,COMP TAP CU 2-2 RUN 8-4 TAP, YC2C4	BURNDY	YC2C4	\$ 0.84

ITEM NO.	ITEM TOTAL	ELDON-DUCKABUSH RECONDUCTOR MASTER MATERIAL LIST REV A - ISSUED FOR BID  			
		MATERIAL DESCRIPTION	VENDOR	PART NO.	UNIT COST
1146	3	CONN.,COMP TAP CU 6-4 RUN 4-4 TAP,YC4C4	ELLIOT	CTH44	\$ 0.90
1177	210	CONDUIT, 2" PVC SCH 80	---	COND2	\$ 2.07
1180	7	CONDUIT, 2" BELL ENDS	---	BELL2	\$ 3.85
1251	2	CONDUIT, PVC ELBOW 90 DEG. 2 IN. RAD 36	---	EL2X36	\$ 23.00
1276	2	ELBOW, 1/0 175 & 220 MIL. TP	ELASTIMOLD	ELA 162LRJS-B-5240-CS782-C	\$ 56.25
1298	1	FAULT IND., UG 100-400 J-TPR/LO	EATON	STLO	\$ 150.71
1362	4	LOCK, PADLOCK 7/8" SHANK SERIES 800, SS	---	1726A	\$ 10.76
1565	1	RACK, REGULATOR	ALUMAFORM	HD2PCAL-14	\$ 2,535.00
1576	2	PEDESTAL, SECONDARY FIBERGLASS	OLDCASTLE	PSPF-101538MG-X	\$ 167.88
1610	3	SWITCH, OH REG. BYPASS DISCONNECT, 15KV	HUBBELL	BPRD061	\$ 2,773.00
1717	3	POLE, 65-2	---	GENERIC	\$ -
1743	1	SECTOR, 1 PHASE FIBERGLASS	POWER DESIGN INC.	CJP1033L2C W/LB	\$ 956.45
1807	94	ARM, EPOXY 18" 2000 LBS	ALUMAFORM	F1CS-MV-A18-BVP-1	\$ -
1808	92	INSULATOR, SPOOL CLEVIS, ANSI 53-4 CLASS	HENDRIX	HPI-53-2	\$ -
1809	204	INSULATOR, SUSPENSION 15kV CLEVIS TONGUE, POLYMER	HENDRIX	DS-15M	\$ -
1810	5	CROSSARM, 8 FOOT, TANGENT, 3000 SERIES	PUPI	TB30009604X2	\$ -
1811	13	CROSSARM, 8 FOOT, DEADEND, 4000 SERIES	PUPI	DA4000096E2B7X2	\$ -
1813	36	CONNECTOR, WEDGE TAP, 336.4-300MCM	CPI	350124	\$ -
1814	52	CONNECTOR, WEDGE TAP, 4/0-4/0	CPI	264115	\$ -
1815	407	GUY GRIP, 18M	PREFORMED	AWDE-4124	\$ -
1816	86	GUY GRIP, AUTOMATIC, 18M, SHORT	HUBBELL	GDE5203	\$ -
1817	10920	GUY WIRE, 18M ALUMOWELD	---	---	\$ -
1818	133	GUY GRIP, AUTOMATIC, 18M, LONG	HUBBELL	GDE5203L	\$ -
1819	4	POLE, 60-2	---	---	\$ -
1820	2	POLE, 60-1	---	---	\$ -
1821	5	POLE, 55-2	---	---	\$ -
1822	10	POLE, 50-2	---	---	\$ -
1823	1	POLE, 45-1	---	---	\$ -
1825	10	POLE, 45-2	---	---	\$ -
1826	3	POLE, 55-1	---	---	\$ -
1827	57	SWINGING ANGLE BRACKET, 1', 5 KIPS	HUGHES BROTHERS	2846.7	\$ -
1828	156	CONNECTOR, WEDGE TAP, 336.4-336.4	CPI	350125	\$ -
1834	16	BOLTED WEDGE HOTLINE TAP CONNECTOR, .414-.858 RUN, .128 TAP	BURNDY	HTC200	\$ -
1835	55	WIRE TIE, 4/0 ACSR, SPOOL INSULATOR TYPE	HUBBELL	LRO4024AS	\$ -
1838	12	STUB POLE, 35-2	---	---	\$ -
1839	3	STUB POLE, 40-2	---	---	\$ -
1841	90489	CONDUCTOR,336.4 ACSR (Merlin)	SOUTHWIRE	---	\$ 1.63
1842	30259.7	CONDUCTOR, BARE, 4/0 ACSR (Penguin)	GENERIC	---	\$ 1.60
1847	30	PIN, TRANSFORMER LEAD, 5/8 BOLT ADAPTER	MACLEAN POWER	J2840Z	\$ -
1848	24	BRACKET, EQUIPMENT MOUNT, 4 HOLE	ALUMAFORM	FC1A-MV-A18-C4	\$ -
1852	12	LINK, EXTENSION, 12 INCH	MACLEAN POWER	CEL12	\$ -
1854	22	INSULATOR, GUY STRAIN, 18", 26.625" OAL	MACLEAN POWER	GCTE2118	\$ -
1855	180	INSULATOR, GUY STRAIN, 96", 2 WHEEL, 21 KIPS	PREFORMED	GSF21-96RR	\$ -

ITEM NO.	ITEM TOTAL	ELDON-DUCKABUSH RECONDUCTOR MASTER MATERIAL LIST REV A - ISSUED FOR BID 			
		MATERIAL DESCRIPTION	VENDOR	PART NO.	UNIT COST
1857	82	ANCHOR, PISA MID STRENGTH, 2- 8", 1" THREADS	HUBBELL	E1021636	\$ -
1859	15	CLAMP, ANCHOR ROD GROUND 5/8 IN., HEX HEAD	GALVAN	JAB58H	\$ -
1860	820	CONDUCTOR, GROUND, #4 SOLID COPPER CLAD STEEL, BLACK JACKET WITH GREEN STRIPE	AFL	CCS01044DBLK	\$ -
1861	21	CONN. CU,AL, 4/0 RUN, #4 TAP	BURNDY	YHD250	\$ -
1862	11	ARRESTER, 10KV, HEAVY DUTY (10KA), TRANSFORMER MOUNTED	MACLEAN POWER	ZHP0100A00100	\$ -
1863	35	CUTOUT, 15KV, 110KV BIL, 200A, 12KV AIC	CHANCE	CP70143PB	\$ -
1864	13	CONNECTOR, WEDGE, .609-.684 RUN, .232-.257 TAP	CPI	350119	\$ -
1865	5	CONNECTOR, WEDGE, .609-.684 RUN, .162-.232 TAP	CPI	350117	\$ -
1866	9	CONNECTOR, WEDGE, .609-.684 RUN, .522-.574 TAP	CPI	350123	\$ -
1867	150	CONDUCTOR, BARE 300MCM 19 STD CU	GENERIC	---	\$ -
1868	13	CONNECTON, WEDGE, .502-.574 RUN, .250-.328 TAP	CPI	264112	\$ -
1869	32	HOT TAP, CU-CU, .162-.745 RUN, .152-.682 TAP	MACLEAN POWER	C 1530	\$ -
1870	11	STIRRUP, ACSR TO CU, 1/0-397.5 ACSR	MACLEAN POWER	HLS-397-LD	\$ -
1872	116	SUSPENSION, ANGLE, .23-.75	MACLEAN POWER	ALS-1-N	\$ -
1873	4	CROSSARM, 23', 3-5/8" x 4-5/8"	BROOKS	23', 3-5/8" x 4-5/8"	\$ -
1874	12	COMPRESSSION, 2 HOLE, 300KCMIL CU	BURNDY	YAZ322NTCFX	\$ -
1876	5	CONNECTOR, WEDGE, .568-.364 RUN, .162-.204 TAP	BURNDY	WCB15	\$ -
1877	11	HOT TAP, CU-CU, .128-.414 RUN, .128-.414 TAP	MACLEAN POWER	C 1520	\$ -
1878	108	SCREW, LAG, 1/2" x 3", FETTER DRIVE	MACLEAN POWER	J8753P	\$ -
1879	15	BRACKET, CONDUIT, 12" T SLOT	MACLEAN POWER	SI-6CSO-12-4WT	\$ -
1880	15	CLAMP, CONDUIT, 2"	MACLEAN POWER	MSTK-2	\$ -
1881	1	TERMINATOR, 15KV, COLD SHRINK, JCN & CN, #2	3M	7642-S-2	\$ -
1882	180	CONDUCTOR, CU #2, 1/C, 7-Str, SD, 600V, HMP	SOUTHWIRE	BLACK	\$ -
1883	1	GUARD, WILDLIFE, CUTOUT, UNIVERSAL	HUBBELL	CO100007	\$ -
1884	12	CONDUCTOR, CU 1/C #2, 7-Str, 600V, Red, THW	SOUTHWIRE	RED	\$ -
1885	1	ARRESTER, 9KV, RISER, EQUIP. ARM MOUNTED, BIRD GUARD	MACLEAN POWER	ZRP0092000100	\$ -
1886	7	CONDUCTOR, CU 1/C #4, 7-Str, 600V, Red, THW	SOUTHWIRE	RED	\$ -
1887	2	CONNECTOR, COMPRESSION, 1 HOLE, 4AWG	BURNDY	YAC4N	\$ -
1888	12	SPLICE, WEATHERPROOF, #2-4/0	ELLIOT	ESG40	\$ -
1889	4	CONDUIT, PVC ELBOW 90 DEG. 2 IN. RAD 24	---	EL2X24	\$ -
1891	10	ARM, EPOXY 38", 2 POSISTION	MACLEAN POWER	G1HDA33814DV1	\$ -
1892	1	SCREW, LAG, 1/2" x 4", FETTER DRIVE	MACLEAN POWER	J8754	\$ -
1896	43	PIN, LONG SHANK, 6", 1" THREAD, 3/4" SHANK	HUBBELL	4705P	\$ -
1897	57	ANCHOR SHACKLE, 3/4 IN, 50 KIP	MACLEAN POWER	ASH-66A	\$ -
1899	180	GUY ATT, POLE PLATE 2 HOLE(DIST)	MACLEAN POWER	EPR877-D7RE	\$ -
1901	37	WIRE TIE, 4 ACSR, SPOOL INSULATOR TYPE	HUBBELL	LRO4006AS	\$ -